

PLUG & FOLD

FLEXIBLE

& FAST

Advanced entry-level offline folding

Folder Express 3000

This flexible, offline, compact folder enables you to produce high-quality fanfolds, fullfolds, long plots or map folds. Easy to install, just plug in and get folding with precision - instantly.



- Produce outstanding-quality, precision-folded documents with ease using proven Es-Te folding technology
- Fold prints of up to 914 mm wide and with an unlimited folding length, making the Folder Express 3000 ideal for CAD and GIS environments
- Produce folded prints up to 30 m/min on this productive device
- Standardise folding with the help of 240 fold package templates - mark your favourites for fast selection
- The 7-inch colour user touch panel with standard tilt function enables easy use
- Produce the narrowest of folds for an expanded application range, using the map fold option
- Add a second catch tray for greater productivity
- Incorporate this ideal offline office companion in your operation, with its low noise emissions and compact design



With the table down for storage, the Folder Express 3000 is even more compact

Canon

Linear folding speed	Up to 30m/min	Delivery capacity	Fanfold: 10 A0 packages (80 g/m ²) Crossfold: 5 A0 (80 g/m ²) Optional: Second catch tray to improve the deposit at the top output: 5 A0 packages (80 g/m ²)
Standard fold programs	240 editable programs, of which 45 standard (DIN A, DIN B, DIN C, Fan Fold Only, AFNOR, JPN, ANSI, ARCH, Mailer)	Power supply	100 - 120 V - 50/60 Hz 200 - 240 V - 50/60 Hz
Document feed	Manual fanfold and crossfold	Power consumption	Folder: Sleep: 1W; Standby: 7,5W; Max: 51W External Power supply: Sleep: 14,6W; Standby: 14,6W; Max: 69W
Document length fanfold only	420 mm - 6000 mm up to 29 layers (80 g/m ² , 210 mm per layer) >6000mm unlimited (no fold area between each 5000 mm folded length)	Dimensions (LxWxH)	Table unfolded: 1158 x 1325 x 1108 mm Table folded: 1158 x 714 x 1108 mm
Document length fanfold & crossfold	420 mm - 2500 mm up to 12 layers fanfold panel (80 g/m ² , 210 mm per layer) Max. 4 cross folds	Shipping dimensions (LxWxH)	1200 x 800 x 1300 mm
Document width	279 - 930 mm	Weight	123 kg
Paper weight (recommended)	60 - 110 g/m ² (75 - 80 g/m ²)	Shipping weight	147 kg
Paper type	Plain paper, bond paper	Operating temperature (recommended)	15 - 35°C (20 - 27°C)
Package width	- 160 - 420 mm (adjustable in 1 mm increments) - 100 - 420 mm with optional map fold license	Operating humidity (recommended)	20 - 80% RH, depending on media type, not-condensing (30 - 60% RH)
Package height	200 - 420 mm (crossfold) (adjustable in 1 mm increments)	Altitude	No limitation
Binding edge	0 - 50 mm (increments of 1 mm)	User interface	7-inch, multi-touch colour
		Acoustic sound pressure	58 dB(A)

© 2022 Canon Production Printing

Canon is a registered trademark of Canon Inc. All other trademarks are the property of their respective owners and hereby acknowledged. No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market. The content of this publication should neither be construed as any guarantee or warranty with regard to specific properties or specifications nor of technical performance or suitability for particular applications. The content of this publication may be subject to changes from time to time without notice. Canon production printing shall not be liable for any direct, indirect or consequential damages of any nature, or losses or expenses resulting from the use of the contents of this publication.